



## Product

- HPBV11 - 1" Female Swivel x 1" Male Extended Lever Ball Valve*
- HPBV114 - 1 1/4" Female Swivel x 1" Male Extended Lever Ball Valve*
- HPBV114X2 - 1 1/4" Female Swivel x 1 1/4" Male Extended Lever Ball Valve*
- HPBV28 - 1" Female Swivel x 28mm Extended Lever Ball Valve*
- HPBV35 - 1 1/4" Female Swivel x 35mm Extended Lever Ball Valve*
- HPBV11FS - 1" Female Swivel x 1" Female Swivel Extended Lever Ball Valve*
- HPBV114FS - 1 1/4" Female Swivel x 1 1/4" Female Swivel Extended Lever Ball Valve*
- EXTKIT - Lever Ball Valve Extension Kit*

## Technical Specification

<i>Max Inlet Pressure (static):</i>	<b>25 Bar</b>
<i>Working Temperature:</i>	<b>-10 to 90°C</b>
<i>Temperature Range: Thread</i>	<b>-20 to 120°C</b>
<i>Standard:</i>	<b>ISO228</b>

	A	B	C	D	E	F	G
HPBV11	1"	1"	88.6	115	115.4	95.3	40
HPBV114	1"	1 1/4"	89	115	121	95.3	40
HPBV114X2	1 1/4"	1 1/4"		115			40
HPBV28	28mm	1"	93.25	115		95.3	40
HPBV35	35mm	1 1/4"	101	115		101.8	40
HPBV11FS	1"	1"	99.36	115	115.4	95.3	40
HPBV114FS	1 1/4"	1 1/4"	108	115	121	101.8	40

## Additional Information

*Solid brass construction*

*Extended lever ball valve handle allows easy access, even with insulation fitted*

*Pressure rating of PN25*

*Working temperature range of -10 to 90°C*

*ISO228 threads*

*Variety of connections to suit all installations*

